

AMK508-D 8 port DVI KVM LCD keyboard drawer



Specification

Model No	AMK508-DB
Construction	Heavy-duty steel
Drawer design	1U, single slide rail LCD KB drawer for 19" cabinet
Display	17.3", 1920x 1080 resolution with tempered glass Option: 17.3", 1600x 900 with tempered glass
Protection	Tempered glass protect LCD screen
Physical security	2 thumb screws to secure LCD monitor
KVM switch	8 port DVI KVM switch
LED indication	Online LED indicates a computer is connecting Select LED indicates the current operation PC port
Keyboard	Industrial keyboard with touchpad Option KB: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US
Power supply	Built-in 60W, 90~264VAC, Operating temp.: -20~70°C
Power consumption	3 watts stand-by, 25 watts in-use
Dimension	442.4x 44x 521.6mm (Wx Hx D)
Weight	11 kgs
KVM cable	8x DVI cables, 8x USB cables

Environmental Factors


	Operating	Non-Operating
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	10%~90%	10%~95%
Approval	CE, FCC, RoHS	

Features

- Meets EIA310c & IEC-3 specification
- 1U, Single slide rail, 17.3" LCD Keyboard drawer
- 8 port DVI KVM switch
- Built-in 17.3" LCD monitor, 1920x 1080 resolution
- Option: 17.3", 1600x 900 LCD monitor
- Industrial keyboard with touchpad
- 1U 521mm short depth and lightweight
- 2 thumb screws to secure 17.3" LCD monitor
- Built-in rail self-locking device
- Tempered glass protect LCD screen

KVM switch

- 8-port rack mountable DVI KVM, USB KB/MS
- 8x DVI-I Female video connectors, and 8x USB type A Female KB/MS connectors
- Support Windows, DOS, Netware, Unix, Linux, IMAC, Power MAC and Sun Micro systems with USB
- Hot plug- add or remove connected computer without powering off the KVM switch or computer
- No software required. Easy computer selection via Front push buttons, keyboard Hot Key



Ordering Information

AMK508-17DBUS

1U, 17.3", 1600x 900, 8-port DVI KVM with 8x DVI/USB cables

AMK508-17WDBUS

1U, 17.3", 1920x 1080, 8-port DVI KVM with 8x DVI/USB cables