




Features

- Meets EIA310c & IEC-3 specification
- 1U, Single slide rail, 17" or 19" LCD KB drawer
- Built-in 17" LCD monitor, 1280x 1024 resolution
Option: 19", 1280x 1024 LCD monitor
- USB or PS2 keyboard with touchpad
- Industrial keyboard with touchpad
- Includes a key-locking mechanism to prevent unauthorized access
- Built-in rail self-locking device
- Tempered glass protect LCD screen



Specification

Model No	AMK801-PB	AMK801-UB
Construction	Heavy-duty steel	
Drawer design	1U, single slide rail LCD KB drawer for 19" cabinet	
Display	17", 1280x 1024 resolution with tempered glass Option: 19", 1280x 1024 with tempered glass	
Protection	Tempered glass protect LCD screen	
Physical security	Key locking mechanism	
Ports switch	VGA D-sub 15 pin, PS2 keyboard, touchpad	VGA D-sub 15 pin, USB keyboard, touchpad
Keyboard	Industrial keyboard with touchpad Option KB: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US	
Power supply	Built-in 60W, 90~264VAC, Operating temp.: -20~70°C	
Power consumption	3 watts stand-by, 25 watts in-use	
Dimension	442.4x 44x 480mm (Wx Hx D)	
Weight	12 kgs	
KVM cable	1.8m PS2 KVM cable	1.8m USB KVM cable

Environmental Factors

	Operating	Non-Operating
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	10%~90%	10%~95%
Approval	CE, FCC, RoHS	

Ordering Information

AMK801-17PBUS

1U, 17", 1280x 1024 LCD, PS2 KB/MS, 1.8m PS2 KVM cable

AMK801-17UBUS

1U, 17", 1280x 1024 LCD, USB KB/MS, 1.8m USB KVM cable

AMK801-19PBUS

1U, 19", 1280x 1024 LCD, PS2 KB/MS, 1.8m PS2 KVM cable

AMK801-19UBUS

1U, 19", 1280x 1024 LCD, USB KB/MS, 1.8m USB KVM cable

Option:

80W, 24~48VDC power supply

Touch screen

DVI-D instead of VGA (D-sub 15-pin)

Sunlight readable (High brightness)

1.8m, 3.0m, 5.0m KVM cable

Keyboard layout: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US



PS2 KVM Cable



USB KVM Cable